

SEDGWICK COUNTY, KANSAS DIVISION OF FINANCE

Purchasing Department 525 N. Main, Suite 823 ~ Wichita, KS 67203

Phone: 316 660-7255 Fax: 316 383-7055 http://sedgwickcounty.org/finance/purchasing.asp

REQUEST FOR PROPOSAL #14-0035 TANDEM AXLE DUMP TRUCKS

ADDENDUM #1

April 22, 2014

The following is to ensure that vendors have complete information prior to submitting a proposal. Here are some clarifications regarding the proposal for three (3) TANDEM AXLE DUMP TRUCKS, for Public Works' use.

Questions and/or statements of clarification are in **bold** font, answers to specific questions are *italicized*.

1. Revised Schedule, RFP page 10.

Distribution of Request for Proposal to interested parties	April 11, 2014
Clarification, Information and Questions submitted in writing by 5:00 P.M. CDT	April 17, 2014
Addendum Issued	April 22, 2014
Sealed proposals due before 1:45P.M. CDT	May 6, 2014
Evaluation Period	May 7-May 28, 2014
Board of Bids and Contracts Recommendation	May 29, 2014
Board of County Commission Award	June 4, 2014

Revision: Sealed Proposal due date was April 29, 2014; Evaluation Period was April 30-May 21, 2014.

2. Specification 5.19.h: Is the Filter minder air restriction to be dash mounted? *Answer: Yes, the filter minder is to be mounted on the dash.*

- 3. Specification 5.29.a: Do you want extended frame rails in front for snow plow mounting? *Answer*: Yes, frame rails shall be extended and capable of mounting snow plow.
- 4. Specification 5.29.f: Shall the removable chipper bar be bolted to frame, or some other type of fastener? Answer: Removable chipper bar shall be bolted to frame.
- 5. Specification 5.34.a: Non-corrosive extended day cab with air ride (hucked cab preferred, or equal or better).

Correction: Added "with air ride" to the description.

6. Specification 5.34.i: Driver seat – air ride high back with arm rests.

Correction: Added "with arm rests" to the description.

- 7. Specification 5.39.d: Bid request for an 88" inside width on the dump body. Most dump body manufactures standard width are 84" to 87". Will you accept a body with an 86" inside width? *Answer:* No. County sand spreaders and brine tanks will not fit in a bed 86" wide. 87" inside width may be accepted but 88" inside width is preferred.
- 8. Specification 5.39.j: AR 400 sides and ends. What is the required thickness on sides and ends? *Answer:* 3/16" AR 400 required.

- 9. **Specification 5.40.e:** Is a wind deflector or a full housing required? *Answer:* Full Housing is required to protect the tarp and spool assembly.
- 10. Specification 5.54.d: The controller needs a RS-232 port for connection to data retrieval/transmission devices, and be specifically capable of interfacing with existing audio video link (AVL) or GPS systems for data logging.

Correction: Changed RS8232 to RS-232.

11. Specification 5.54.d: What is AVL?

Answer: AVL means Automotive Vehicle Locater or GPS.

- 12. **5.54.i:** Will you accept diagnostic and calibration of spreader controls that do not require a key board? Answer: It is acceptable to have controls that do not require a keyboard.
- 13. 5.55.c: Does "the plow control will be dual axis with Power Float" refer to plow balance or weight control of blade down pressure?

Answer: Yes. We must control weight of blade to surface.

14. 5.57.a: Does the trailer use truck hydraulics or self contained?

Answer: The trailer uses truck hydraulics. Trailer hydraulic hoses attach at the sand spreader hydraulic connections.

Firms interested in submitting a proposal, must respond with complete information and all supplementary materials and **deliver on or before 1:45 p.m.** (CDT), Tuesday, May 6, 2014. Late proposals will not be accepted and will not receive consideration for final award.

Vendors are responsible for checking the website and acknowledging any addenda on the proposal response form.

Gunda Angelica Purchasing Agent