



SEDGWICK COUNTY, KANSAS
DIVISION OF FINANCE
Purchasing Department
525 N. Main, Suite 823 ~ Wichita, KS 67203

Phone: 316 660-7255 Fax: 316 383-7055
<http://sedgwickcounty.org/finance/purchasing.asp>

REQUEST FOR PROPOSAL
#14-0044
EXTENDED CAB TANDEM WINCH TRUCK

ADDENDUM #1

April 25, 2014

The following is to ensure that vendors have complete information prior to submitting a proposal. Here are some clarifications regarding the proposal for one (1) EXTENDED CAB TANDEM WINCH TRUCK, for Public Works' use.

Questions and/or statements of clarification are in **bold** font, answers to specific questions are *italicized*.

- **Specification 5.13.2.a: Is 345 HP acceptable?**
Answer: Yes. Six (6) cylinder diesel 345 HP is acceptable.
- **Specification 5.13.2.b: Does the torque have to be 1150 ft lbs?**
Answer: No. 1000 lb/ft torque at rated rpm is acceptable.
- **Specification 5.13.2.i: Is the filter minder air restriction indicator dash or filter mounted?**
Answer: Filter minder air restriction indicator shall be dash mounted.
- **Specification 5.13.3: Dual power steering with 12,000 lb capacity axle?**
Answer: Dual steering with 12,000 lb axle is not required; however, power steering is required.
- **Specification 5.13.4: Is Dana Axle acceptable?**
Answer: Yes. Dana Axle is acceptable
- **Specification 5.13.5: Please clarify 12,000 lbs taper leaf with shock absorbers**
Clarification: Minimum 12,000 capacity springs with heavy duty shock absorbers will be accepted.
- **Specification 5.13.12.a:**
 - **Is heavy duty 120,000 psi yield required?**
ANSWER: 110,000 psi is acceptable.
 - **What is RBM?**
Answer: RBM is defined as Resisting Bending Motion to be 2,132,000 in-lbs per rail
 - **Do you want frame insert for winch area?**
Answer: No inserts
 - **Do you want double frame truck?**
Answer: No double frames
- **Specification 5.13.17.x: Please clarify body builder wiring and end of frame wiring.**
Clarification: Chassis builder will provide wiring for body builder to install power take off (PTO) and lights at end of frame.

- **Specification 5.13.21.j: Five (5) lb fire extinguisher mounted inside cab.**
CORRECTION: Change from 1 lb to 5 lbs. Truck shall be DOT approved.
- **Specification 5.13.23.c:**
 - **Is Planetary 30,000 winch acceptable?**
Answer: Yes, Planetary 30,000 winch is acceptable.
 - **Is Braden winch acceptable?**
Answer: No, Braden winch is not acceptable.
- **Specification 5.13.23.g: Please clarify line guide on winch with cable roller on uprights.**
Clarification: Uprights on back of truck are used as guides for winch cable. Roller on these uprights is needed to protect cable from rubbing on bed.
- **Specification 5.13.23.r: Do you require that much cable?**
Answer: Yes, ¾" winch cable approximately 313 feet with tail chain required.
- **Specification 5.13.23.s.: Clarify Strobes on line guide.**
Clarification: Strobes to be mounted in skirt of bed and at rear of truck cab. May be mounted on guides, headache rack, cab protector, just so they are visible.
- **Specification 5.13.24.f: Clarify tail roller specs.**
Clarification: Tail roller to be 6" diameter, width of truck bed, thick enough to support cable while rolling in and out for many years.

Firms interested in submitting a proposal, must respond with complete information and all supplementary materials and **deliver on or before 1:45 p.m. (CDT), Tuesday, May 6, 2014.** Late proposals will not be accepted and will not receive consideration for final award.

Vendors are responsible for checking the website and **acknowledging any addenda on the proposal response form.**

Gunda Angelica
Purchasing Agent