

## REQUEST FOR BID #14-0049 MOWING DECKS

## ADDENDUM #1

May 1, 2014

The following is to ensure that vendors have complete information prior to submitting a proposal. Here are some clarifications regarding the bid for three (3) ten foot Flex-Wing Rotary Cutters and one (1) fifteen foot Flex-Wing Rotary Cutter, for Public Works' use.

Questions and/or statements of clarification are in **bold** font, answers to specific questions are *italicized*.

## 1. Section 3: Timeline revised; bid due date changed to May 13, 2014

. Section 5. Thirefine revised, but due date changed to May 15, 2014	
Distribution of Request for Bid to interested parties	April 22, 2014
Clarification, Information and Questions submitted in writing by 5:00 p.m. CST	April 25, 2014
Addendum Issued	May 1, 2014
Bids due before 1:45 p.m. CDT	May 13, 2014
Evaluation Period	May 14, 2014
Board of Bids and Contracts Recommendation	May 15, 2014
Board of County Commission Award	May 21, 2014

## 2. **1.09.1.a.:** Is a cutting width of 126" acceptable instead of 125"? *Answer: Yes. 126" cutting width is acceptable.*

3. 1.09.1.b.: Is a cutting height range of 2" low to maximum of 14" or a cutting height range of 1.25" to 16.25" acceptable?

Answer: No. The cutting height shall be 1" low cut to a maximum of 16"

- 4. 1.09.1.d.: Is the listed weight a maximum or minimum weight? *Answer: Minimum. Minimum weight is 5,650 lbs.*
- 5. **1.09.4.c.:** Is a single domed deck mower type acceptable? Answer: No, a domed deck mower type is not acceptable.
- 6. **1.09.6.f.:** Is a heavy duty cast dog bone pan and/or round stump jumper acceptable? . *Answer: Yes. A heavy duty cast dog bone pan and/or round stump jumper is acceptable.*
- 7. **1.09.7a.:** Are 24" x 8" x 14" or 25.5" x 8" x 14" tire dimensions acceptable? Answer: No. 26" x 9" x 14.5" severe ag duty 24 ply tire (prefer foam filled or run flat tire), new tire and new wheels required.

8. 1.09.8.a.: Is a spring suspension instead of air cushion acceptable? Are rubber mounted shock absorbers full independent rear suspensions acceptable? Are factory supplied rear mower suspensions acceptable? Answer: No. Axles must be engineered to absorb shock during transportation and operation. Air cushion with shock absorbers at 4 points required.

Firms interested in submitting a bid must respond with complete information and all supplementary materials and **deliver on or before 1:45 p.m. (CDT), Tuesday, May 13, 2014.** Late bids will not be accepted and will not receive consideration for final award.

Vendors are responsible for checking the website and acknowledging any addenda on the bid response form.

Gunda Angelica Purchasing Agent