

SEDGWICK COUNTY, KANSAS DIVISION OF FINANCE PURCHASING DEPARTMENT 525 N. Main, Suite 823 ~ Wichita, KS 67203

Phone: 316 660-7255 Fax: 316 383-7055 www.sedgwickcounty.org/finance/purchasing.asp

REQUEST FOR BID #15-0032 FIVE (5) TANDEM AXLE DUMP TRUCKS

March 18, 2015

Sedgwick County, Kansas (hereinafter referred to as "County") is seeking to obtain bids from vendors to provide five (5) TANDEM AXLE DUMP TRUCKS, for Public Work's use. It is anticipated that an official contract and/or purchase order will be issued after Board of County Commission approval of the recommended bid. It should be noted, however, that the County cannot guarantee the purchase of the product described herein.

Carefully review this Request for Bid. It provides specific technical information necessary to aid participating firms in formulating a thorough response. To ensure that vendors have complete information prior to submitting a bid, a pre-bid meeting has been scheduled for March 25, 2015 beginning at 11:00 a.m. CDT at W. 1021 Stillwell St., Fleet Management. Should firms elect to participate, one (1) complete original, and one (1) electronic copy on disc or USB of the entire document with any supplementary materials must be completed and returned to:

Gunda Angelica Sedgwick County Purchasing Department 525 N. Main St., Suite 823 Wichita, KS 67203

SUBMITTALS are due **NO LATER THAN 1:45 P.M. CDT, April 7, 2015.** Responses must be <u>sealed and marked on</u> the lower left-hand corner with the firm name and address, bid number, and bid due date. Late or incomplete responses will not be accepted and will not receive consideration for final award. The time stamp clock in the Purchasing Department will determine the time of receipt.

Kmb Argeh

Gunda Angelica Purchasing Agent

1. ABOUT THIS DOCUMENT

The nature of this work is for a public entity and will require the expenditure of public funds and/or use of public facilities, therefore the successful proposer will understand that portions (potentially all) of their bid may become public record at any time after receipt of bids. Bid responses, purchase orders and final contracts are subject to public disclosure after award. All confidential or proprietary information should be clearly denoted in bid responses and responders should understand this information will be considered prior to release, however no guarantee is made that information will be withheld from public view.

2. GENERAL & BACKGROUND INFORMATION

Sedgwick County, located in south-central Kansas, is one of the most populous of Kansas' 105 counties with a population estimated at more than 503,000 persons. It is the sixteenth largest in area, with 1,008 square miles, and reportedly has the second highest per capita wealth among Kansas counties. Organizationally, the County is a Commission/Manager entity, and hosts or provides a full range of municipal services, e.g. – public safety, public works, criminal justice, recreation, entertainment, cultural, human/social, and education. In accordance with the specifications outlined here, it is the intent to receive bids to provide five (5) TANDUM AXLE DUMP TRUCKS. Trucks shall have front tilting hood and 15 foot, 12 cubic yard dump bed with 126" telescopic hoist. Three of the five trucks shall have a hitch on the rear, 3" pintle type, capable of towing a 40,000 pound rollback trailer.

3. MINIMUM QUALIFICATIONS

The successful proposer must:

- 3.1 Have experience with the equipment and technical ability; and have personnel and facilities to properly complete, coordinate and administer the contract, if awarded.
- 3.2 Have proven ability to provide high quality service(s) and/or product(s) within the specifications, mandatory requirements, miscellaneous instructions and conditions as outlined in this and future related documents.
- 3.3 Provide product/services following all applicable federal, state, and local laws, regulations, and ordinances.

4. GENERAL REQUIREMENTS

- 4.1 Must be new current production model.
- 4.2 Provide manufacturer name, model proposed and include specifications.
- 4.3 Provide a lead time for production.

5. MINIMUM REQUIREMENTS AND SPECIFICATIONS

The following specifications are provided for procurement of five (5) Tandem Axle Dump Trucks, for Public Works.

- 5.1 Any items appearing in the equipment manufacturer's regular published specifications furnished by the proposers are assumed included in the proposer's response.
- 5.2 All items proposed to be factory installed unless authorized by Sedgwick County Fleet Management.
- 5.3 Price bid must include delivery to Sedgwick County Fleet located at 1021 W. Stillwell St., Wichita, Kansas 67213.
- 5.4 After award and prior to delivery, an appointment must be made to deliver equipment to Fleet Management, 1021 W. Stillwell St., Wichita, KS. Please contact Penny Poland at 316-660-7477. Deliver to Rex Victory's attention.
- 5.5 Fleet Management will not accept ownership until equipment has been inspected for compliance with specifications below and Manufacture's Statement of Origin (MSO) has been delivered.
- 5.6 Manufacturer's ordering form must be included with bid submittal for the purpose of ordering the vehicles.
- 5.7 Provide one complete set of manuals including parts manual, repair and maintenance manual, including wiring schematics. Manuals shall be invoiced separately.
- 5.8 Operator manuals and parts manuals for all equipment mounted on vehicle shall be supplied; i.e., salt spreader control, plow and hoist control, trailer hitch, etc.
- 5.9 Provide complete diagnostic software, hardware or adapters, and scan tool to diagnose and repair vehicle trouble codes. If software is required to adjust and modify the electrical outputs for accessory equipment it shall be included as a part of this bid. If software requires upgrades, it shall be included for three (3) years as part of this bid; i.e., Cummins Insite, Allison software, etc.
- 5.10 Contract pricing for labor and parts will be established for three (3) years. This contract will cover any work or repairs needed that do not fall under warranty work and will include like equipment owned by the County.
- 5.11 The winning bidder will provide operator training and assistance with calibration of the systems at a location to be

determined by the County

- 5.12 Trucks shall meet all current DOT regulations and all lighting shall meet DOT regulations.
- 5.13 Trucks shall meet current EPA emissions standards.
- 5.14 Proposed trucks shall be compatible with Sedgwick County owned equipment including, but not limited to: Wellar Shoulder Machine, Etnyer Chip Spreader and all Snow Removal Equipment, Flink, Henderson, Warren & Monroe sand spreaders, Henke snow plows. Sedgwick County may require bidders to bring a truck chassis to one of Sedgwick County's Yards to verify compatibility with all public works equipment to be used with these trucks.
- 5.15 Tandem axle dump trucks with front tilting hood and 15 foot, 12 cubic yard dump bed with 126" telescopic hoist.
- 5.16 All requirements and specifications are intended to be minimum specifications and any additions, deletions, or variations from the following specifications must be noted by the vendor on the bid response form. Manufacturer's standard equipment presumed to be included unless otherwise specified. Vendor shall indicate in the "Yes/No" column if their bid complies on each specific item. Any additions, deletions, or variations from the following specifications should be clearly identified and detailed in a response using corresponding specification number.

SPECIFI	CATIONS	MEETS SPECIF	ICATION
5.16.1	Transmission:	Yes	No
a.	Allison 3000 RDS with five (5) year extended warranty, required		
b.	Transynd Synthetic oil		
с.	Auto-Neutral		
d.	Push button shift control mounted in/on dash.		
e.	Power take off (PTO) mount decided by dump body manufacturer. RH required		
5.16.2	Engine:		
a.	Six (6) cylinder diesel with minimum 345 horse power (hp)		
b.	1,000 lb/ft. torque at rated rpm as required by Allison Transmission		
с.	Engine compression brake		
d.	Turbocharged		
e.	Engine block heater		
f.	Heavy duty radiator with extended life coolant tested -34 degrees F.		
g.	Two (2) speed fan hub		
h.	Heavy duty dry element air filter. Inside /outside air intake capable of using in snow		
	without restricting intake air. Filter minder air restriction indicator		
i.	Engine safety shutdown for low oil pressure, high coolant temperature and low coolant		
	level.		
5.16.3	Steering: Dual power steering gears: 20000 Sheppard M100P		
5.16.4	Front Axle:		
a.	20,000 lb. setback axle		
b.	10-hole piloted hubs. Low maintenance hub package with adjustment free bearings.		
5.16.5	Front Springs: 20,000 lb. taper leaf with shock absorbers		
5.16.6	Rear Axle:		
a.	40,000 lb. axle with full lock differential on rear and magnetic drain plugs in both		
b.	Heavy Duty drive line		
с.	10 hole piloted hubs		
d.	Gear ratio to be determined by manufacturer (capable of maintaining normal highway		
	speed of 72 mph fully loaded estimated 5.29 gear ratio)		
e.	Asphalt dump brake chamber clearance. Brake chambers must clear rollers on County		
	owned road widener. Weiler brand machine required.		
f.			
5.16.7	Rear Suspension: Tandem Chalmers 854-40-H-HS 40,000 lbs. suspension		
5.16.8	Brakes:		
a.	Front-16 $\frac{1}{2}$ x 6" cam brakes with automatic slack adjuster		

 16 ½ x 7" cam brakes with automatic slack adjuster system air brakes with air tank drain valves. ng spring brakes, both axles 3030 high output dual E - Equal to or better than Michelin XYZ-2 315/80r 22.5 (20 ply) or Bridgestone 2 22.5 x 9 aluminum wheel pilot mount - Equal to or better than Michelin 11R-22.5-XDA-HT (14 ply) or Bridgestone 16 Yeas 2.5 x 8.25 aluminum wheel pilot mount with hand holes el Seals: - heel seals to be extended life oil type for bearings. Low maintenance shields all wheels Tank: (1) Aluminum 100 gallon fuel tank passenger side 10 DEF tank mounted passenger side ne: y duty steel 3/8 inch C-channel frame rails. Section modulus is 17.80; resisting ing movement (RBM) is 2,132,000 in-lbs per rail. 100 PSI strength e 138" Frame left side, (drivers side), to allow for controls for dump body ty owned snow plow frame to be removed from old trucks and installed on new trucks inning bidder ovable chipper bar shall; i.e., be manufactured and mounted on rear of two (2) units as 		
ng spring brakes, both axles 3030 high output dual i: - Equal to or better than Michelin XYZ-2 315/80r 22.5 (20 ply) or Bridgestone) - 22.5 x 9 aluminum wheel pilot mount - Equal to or better than Michelin 11R-22.5-XDA-HT (14 ply) or Bridgestone IEL - 22.5 x 8.25 aluminum wheel pilot mount with hand holes el Seals: heel seals to be extended life oil type for bearings. Low maintenance shields all wheels Tank: (1) Aluminum 100 gallon fuel tank passenger side llon DEF tank mounted passenger side ne: y duty steel 3/8 inch C-channel frame rails. Section modulus is 17.80; resisting ng movement (RBM) is 2,132,000 in-lbs per rail. 000 PSI strength e 138'' Frame left side, (drivers side), to allow for controls for dump body ty owned snow plow frame to be removed from old trucks and installed on new trucks inning bidder ovable chipper bar shall; i.e., be manufactured and mounted on rear of two (2) units as		
 Equal to or better than Michelin XYZ-2 315/80r 22.5 (20 ply) or Bridgestone 22.5 x 9 aluminum wheel pilot mount Equal to or better than Michelin 11R-22.5-XDA-HT (14 ply) or Bridgestone 22.5 x 8.25 aluminum wheel pilot mount with hand holes el Seals: theel seals to be extended life oil type for bearings. Low maintenance shields all wheels Tank: (1) Aluminum 100 gallon fuel tank passenger side llon DEF tank mounted passenger side theel y duty steel 3/8 inch C-channel frame rails. Section modulus is 17.80; resisting ing movement (RBM) is 2,132,000 in-lbs per rail. 000 PSI strength e 138" Frame left side, (drivers side), to allow for controls for dump body ty owned snow plow frame to be removed from old trucks and installed on new trucks inning bidder ovable chipper bar shall; i.e., be manufactured and mounted on rear of two (2) units as 		
 Equal to or better than Michelin XYZ-2 315/80r 22.5 (20 ply) or Bridgestone 22.5 x 9 aluminum wheel pilot mount Equal to or better than Michelin 11R-22.5-XDA-HT (14 ply) or Bridgestone 12L 22.5 x 8.25 aluminum wheel pilot mount with hand holes el Seals: wheel seals to be extended life oil type for bearings. Low maintenance shields all wheels Tank: (1) Aluminum 100 gallon fuel tank passenger side llon DEF tank mounted passenger side ng movement (RBM) is 2,132,000 in-lbs per rail. 000 PSI strength e 138" Frame left side, (drivers side), to allow for controls for dump body ty owned snow plow frame to be removed from old trucks and installed on new trucks inning bidder ovable chipper bar shall; i.e., be manufactured and mounted on rear of two (2) units as 		
 22.5 x 9 aluminum wheel pilot mount Equal to or better than Michelin 11R-22.5-XDA-HT (14 ply) or Bridgestone IEL 22.5 x 8.25 aluminum wheel pilot mount with hand holes el Seals: cheel seals to be extended life oil type for bearings. Low maintenance shields all wheels Tank: (1) Aluminum 100 gallon fuel tank passenger side llon DEF tank mounted passenger side ne: y duty steel 3/8 inch C-channel frame rails. Section modulus is 17.80; resisting ing movement (RBM) is 2,132,000 in-lbs per rail. 000 PSI strength e 138" Frame left side, (drivers side), to allow for controls for dump body ty owned snow plow frame to be removed from old trucks and installed on new trucks inning bidder ovable chipper bar shall; i.e., be manufactured and mounted on rear of two (2) units as 		
 - 22.5 x 9 aluminum wheel pilot mount - Equal to or better than Michelin 11R-22.5-XDA-HT (14 ply) or Bridgestone IEL - 22.5 x 8.25 aluminum wheel pilot mount with hand holes el Seals: - el Seals: - el seals to be extended life oil type for bearings. Low maintenance - shields all wheels Tank: (1) Aluminum 100 gallon fuel tank passenger side Ilon DEF tank mounted passenger side ne: y duty steel 3/8 inch C-channel frame rails. Section modulus is 17.80; resisting ing movement (RBM) is 2,132,000 in-lbs per rail. 00 PSI strength e 138" - Frame left side, (drivers side), to allow for controls for dump body ty owned snow plow frame to be removed from old trucks and installed on new trucks inning bidder 		
 Equal to or better than Michelin 11R-22.5-XDA-HT (14 ply) or Bridgestone IEL 22.5 x 8.25 aluminum wheel pilot mount with hand holes el Seals: wheel seals to be extended life oil type for bearings. Low maintenance shields all wheels Tank: Aluminum 100 gallon fuel tank passenger side DEF tank mounted passenger side y duty steel 3/8 inch C-channel frame rails. Section modulus is 17.80; resisting ing movement (RBM) is 2,132,000 in-lbs per rail. OO PSI strength e 138" Frame left side, (drivers side), to allow for controls for dump body ty owned snow plow frame to be removed from old trucks and installed on new trucks inning bidder 		
IEL - 22.5 x 8.25 aluminum wheel pilot mount with hand holes el Seals: theel seals to be extended life oil type for bearings. Low maintenance shields all wheels Tank: (1) Aluminum 100 gallon fuel tank passenger side 10 DEF tank mounted passenger side ne: y duty steel 3/8 inch C-channel frame rails. Section modulus is 17.80; resisting ing movement (RBM) is 2,132,000 in-lbs per rail. 00 PSI strength e 138" Frame left side, (drivers side), to allow for controls for dump body ty owned snow plow frame to be removed from old trucks and installed on new trucks inning bidder ovable chipper bar shall; i.e., be manufactured and mounted on rear of two (2) units as		
 - 22.5 x 8.25 aluminum wheel pilot mount with hand holes el Seals: wheel seals to be extended life oil type for bearings. Low maintenance shields all wheels Tank: (1) Aluminum 100 gallon fuel tank passenger side (1) Aluminum 100 gallon fuel tank passenger side (1) Aluminum 100 gallon fuel tank passenger side y duty steel 3/8 inch C-channel frame rails. Section modulus is 17.80; resisting ing movement (RBM) is 2,132,000 in-lbs per rail. y OPSI strength e 138" Frame left side, (drivers side), to allow for controls for dump body ty owned snow plow frame to be removed from old trucks and installed on new trucks inning bidder y ovable chipper bar shall; i.e., be manufactured and mounted on rear of two (2) units as 		
el Seals: theel seals to be extended life oil type for bearings. Low maintenance shields all wheels Tank: (1) Aluminum 100 gallon fuel tank passenger side llon DEF tank mounted passenger side ne: y duty steel 3/8 inch C-channel frame rails. Section modulus is 17.80; resisting ing movement (RBM) is 2,132,000 in-lbs per rail. 00 PSI strength e 138" Frame left side, (drivers side), to allow for controls for dump body ty owned snow plow frame to be removed from old trucks and installed on new trucks inning bidder ovable chipper bar shall; i.e., be manufactured and mounted on rear of two (2) units as		
wheel seals to be extended life oil type for bearings. Low maintenance shields all wheels Tank: (1) Aluminum 100 gallon fuel tank passenger side Ilon DEF tank mounted passenger side ne: y duty steel 3/8 inch C-channel frame rails. Section modulus is 17.80; resisting ing movement (RBM) is 2,132,000 in-lbs per rail. 000 PSI strength e 138" Frame left side, (drivers side), to allow for controls for dump body ty owned snow plow frame to be removed from old trucks and installed on new trucks inning bidder ovable chipper bar shall; i.e., be manufactured and mounted on rear of two (2) units as		
shields all wheels Tank: (1) Aluminum 100 gallon fuel tank passenger side llon DEF tank mounted passenger side ne: y duty steel 3/8 inch C-channel frame rails. Section modulus is 17.80; resisting ing movement (RBM) is 2,132,000 in-lbs per rail. 00 PSI strength e 138" Frame left side, (drivers side), to allow for controls for dump body ty owned snow plow frame to be removed from old trucks and installed on new trucks inning bidder ovable chipper bar shall; i.e., be manufactured and mounted on rear of two (2) units as		
Tank: (1) Aluminum 100 gallon fuel tank passenger side Ilon DEF tank mounted passenger side ne: y duty steel 3/8 inch C-channel frame rails. Section modulus is 17.80; resisting ing movement (RBM) is 2,132,000 in-lbs per rail. 000 PSI strength e 138" Frame left side, (drivers side), to allow for controls for dump body ty owned snow plow frame to be removed from old trucks and installed on new trucks inning bidder ovable chipper bar shall; i.e., be manufactured and mounted on rear of two (2) units as		
 1) Aluminum 100 gallon fuel tank passenger side 10 DEF tank mounted passenger side 11 DEF tank mounted passenger side 12 Def tank mounted passenger side 13 of the second seco		
Ilon DEF tank mounted passenger side ne: y duty steel 3/8 inch C-channel frame rails. Section modulus is 17.80; resisting ing movement (RBM) is 2,132,000 in-lbs per rail. 00 PSI strength e 138" Frame left side, (drivers side), to allow for controls for dump body ty owned snow plow frame to be removed from old trucks and installed on new trucks inning bidder ovable chipper bar shall; i.e., be manufactured and mounted on rear of two (2) units as		
y duty steel 3/8 inch C-channel frame rails. Section modulus is 17.80; resisting ing movement (RBM) is 2,132,000 in-lbs per rail. 000 PSI strength e 138" Frame left side, (drivers side), to allow for controls for dump body ty owned snow plow frame to be removed from old trucks and installed on new trucks inning bidder ovable chipper bar shall; i.e., be manufactured and mounted on rear of two (2) units as		
y duty steel 3/8 inch C-channel frame rails. Section modulus is 17.80; resisting ing movement (RBM) is 2,132,000 in-lbs per rail. 000 PSI strength e 138" Frame left side, (drivers side), to allow for controls for dump body ty owned snow plow frame to be removed from old trucks and installed on new trucks inning bidder ovable chipper bar shall; i.e., be manufactured and mounted on rear of two (2) units as		
Ing movement (RBM) is 2,132,000 in-lbs per rail. 00 PSI strength e 138" Frame left side, (drivers side), to allow for controls for dump body ty owned snow plow frame to be removed from old trucks and installed on new trucks inning bidder ovable chipper bar shall; i.e., be manufactured and mounted on rear of two (2) units as		
00 PSI strength e 138" Frame left side, (drivers side), to allow for controls for dump body ty owned snow plow frame to be removed from old trucks and installed on new trucks inning bidder ovable chipper bar shall; i.e., be manufactured and mounted on rear of two (2) units as		
e 138" Frame left side, (drivers side), to allow for controls for dump body ty owned snow plow frame to be removed from old trucks and installed on new trucks nning bidder ovable chipper bar shall; i.e., be manufactured and mounted on rear of two (2) units as		
Frame left side, (drivers side), to allow for controls for dump body ty owned snow plow frame to be removed from old trucks and installed on new trucks inning bidder ovable chipper bar shall; i.e., be manufactured and mounted on rear of two (2) units as		
ty owned snow plow frame to be removed from old trucks and installed on new trucks nning bidder ovable chipper bar shall; i.e., be manufactured and mounted on rear of two (2) units as		
inning bidder ovable chipper bar shall; i.e., be manufactured and mounted on rear of two (2) units as		
ovable chipper bar shall; i.e., be manufactured and mounted on rear of two (2) units as		
		1
county owned equipment; Etnyer chip spreader. Three (3) units shall have Pintle hitch		
ble of towing county owned trailers & equipment with air brakes.		
l and Fenders:		-
glass tilting front hood and fenders with stationary grill		
mud flaps on fenders		
t Bumper: Painted steel heavy duty		
rical:		
mp alternator		
lt system		
e (3) 12-volt maintenance free group 31 batteries. 2,100 cold cranking amps (CCA)		
Compressor:		
cu. ft. compressor		1
tor system saver 1200 air drier		
& Equipment:		
corrosive extended day cab (hucked cab preferred, equal or better) with air ride		1
bumper to back of cab (BBC)		
glass hood		
on and doors keyed alike. 3 key sets each vehicle		
		1
y duty door minges		
d safety glass		
		1
d safety glass		1
d safety glass er door locks	+	
d safety glass er door locks er windows		
d safety glass er door locks er windows er seat – air ride high back with arm rests	 	
d safety glass er door locks er windows er seat – air ride high back with arm rests enger seat – standard with tool box under seat		
	& Equipment: corrosive extended day cab (hucked cab preferred, equal or better) with air ride bumper to back of cab (BBC) glass hood on and doors keyed alike. 3 key sets each vehicle / duty door hinges l safety glass r door locks	& Equipment:

n.	Factory air conditioning/heating system	
0.	Stainless steel mirrors 7" x 16" with heating element	
р.	Two (2) convex 8" heated mirrors centered under mirror bracket	
q.	All mirror fasteners stainless steel	
r.	Two air horns on top of cab preferred	
s.	Radio – AM/FM with weather band	
t.	Cab prewired for county 2-way radio (12 volt)	
u.	Switch & wiring for PTO	
v.	Truck, prewired from factory for snow plow lights with remote turn signals, and shall have	
	snow plow lights mounted on hood with non-corrosive brackets. Equal to or better than	
	Truck Lite ATL with high/low beam and turn signal lights.	
w.	Electric windshield wipers with intermittent feature. Truck lights turn on when wipers are	
	on.	
5.16.18	Instrument Package:	
a.	Electric speedometer & tachometer primary readout to be mph.	
b.	Hour meter	
с.	Voltmeter	
d.	Dual air pressure	
e.	Engine oil pressure	
f.	Water temp	
g.	Transmission temperature	
h.	Air filter restrictor	
i.	Fuel level gauge and DEF level and warning gauge	
5.16.19	Warning package with warning lights and buzzer:	
a.	High water temperature	
b.	Low oil pressure	
с.	Low air pressure	
d.	High beam	
e.	Turn signal indicators	
f.	Headlights halogen	
g.	Marker lights (5) International Code Council (ICC) approved	
h.	Dual sun visors inside	
5.16.20	Vehicle Color:	
a.	Exterior: white	
b.	Interior: dark blue or gray	
5.16.21	Accessories:	
a.	Cab lights	
b.	Back-up lights	
с.	Turn signals	
d.	Clearance lights	
e.	Snow plow lights and non-corrosive brackets	
f.	Exterior grab handles (one left and one right)	
g.	Hour meter oil pressure activated	
h.	Steps on right side under cab	
i.	Exhaust single vertical muffler with stainless steel guard on right side with particulate	
	filter mounted horizontally under or behind step	
j.	Chrome muffler and curved standpipe to be mounted as close as possible to cab, and shall	
	clear dump body to prevent damage to exhaust system.	
k.	1 lb. Fire extinguisher mounted inside cab	
1.	First aid kit	
m.	Emergency triangle flare kit	
n.	Plug in for cell phone charger	

5.16.22	Dump Beds:		
a.	Telescopic front mount type hoist		
b.	Air operated tailgate latch		
с.	15' Dump Body (12-yd) bed		
d.	15'x 87'' inside with 44'' tailgate		
e.	12" rear corner post		
f.	Sides 48" minimum at header to 44" at tailgate		
g.	50'' tall header		
<u> </u>	3/16" boxed top rail		
i.	3/16" AR 400 floor		
i	3/16" AR 400 sides and ends		
k.			
1.	1/4"x 2" flat strap walk rails		
	Lift loop on nine-panel 44" tailgate		
n.	1-1/2" diameter hinge pin		
0.	Tailgate ears with grease fittings		
р.	Tailgate latch cross shaft capable of receiving lube/grease		
1	Inside step right front corner of bed		
q. r.	12" spreader apron		
S.	Long tailgate chains		
5. t.	Body with tie downs to retain sand spreader		
u.	Three (3) each vertical oblong holes for lighting Truck Lite (T/L)-60 both sides of tailgate		
u.	on rear corner post		
v.	Standard Department of Transportation (DOT) location for clearance marker and ID		
۷.	markers size T/L-10 ^{1/2} -cab protector		
w.	One (1) T/L 60 strobe to be mounted in center of shield facing forward. [Total of three, (3)		
w.	strobes on front of cab shield]		
5.16.23	Mesh tarp Roll-Rite 6000 system or better		
	The tarp capable of being operated within the cab of the truck		
a. b.	The system powered by chrome plated, direct drive gear motor that includes a three (3)		
υ.	year warranty against parts wear out		
с.	System constructed primarily of polished aluminum alloys		
d.	Provide a tension bow that tucks the tarp down behind the cab protector system		
e.	Provide a one-piece wind full housing deflector to protect the tarp and spool assembly		
f.	Utilize compact pivot assemblies powered by spiral torsion springs		
 g.	Tandem axle truck bodies fitted with pivot assemblies containing four (4) springs per side		
5.16.24	Lighting:		
a.	Chassis to have factory installed auxiliary lighting package harness installed terminated		
u.	rear of frame with weather pack style plug for standard lighting. Extra 12" of wiring for		
	easy repair of lights.		
b.	Stop turn signal (SST)/Marker backup		
c.	Two switched hot wires 20 amp. rated for auxiliary lighting rocker style lighted switches		
•••	dash mounted.		
d.	All clearance and ID markers on dump body, 2-1/2" sealed T/L- 10 LED hi count lamps		
e.	Grote part number G-1032 red, equal or better		
f.	Grote part number G-1033 amber, equal or better		
g.	Rear red stop/turn signal on dump body sides, oval sealed T/L-60LED hi count		
<u> </u>	Grote part number G-6002 red or equal, equal or better, mounted one on each side of		
	tailgate		
i.	Back-up lamps on dump body oval sealed T/L-60 clear		
j.	Grote part number 62231, equal or better, mounted one on each side of tailgate		
J.			

5.16.25	Strobes: Amber oval sealed LED strobes Random quad flash T/L-60 Federal signal part	
5.10.25	number 607101-02 equal to or better than mounted on each side of tail-gate, each angled	
	corner of cab protector, and center of cab protector	
5.16.26	Mud Flaps & Fenders:	
a.	Mud flaps on rear of body mounted on quick release holders.	
b.	¹ / ₄ fenders mounted in front of rear wheels	
c.	Back-up alarm 112db Federal Signal part number 210335, equal or better	
5.16.27	Auto Lube System Installed:	
a.	Operated by vehicle electrical supply	
b.	Hold 4lb. (2 liter) National Lubricating Grease Institute (NLGI) #2 grease delivered full	
с.	Fully adjustable interval timing setting	
d.	Operating pressure of 248 BAR (3,600psig)	
5.16.28	Central Hydraulic System:	
a.	The central hydraulic system capable of operating:	
u.	1. A telescopic hoist	
	2. A material spreader	
	3. A reversible snow plow	
b.	All components provided, capable of continual operating at pressures in excess of 2500 psi.	
5.16.29	Hydraulic Pump:	
	Parker PAVC65 pressure and flow sensing piston pump with adjustable standby pressure	
a. b.	Pump to be direct drive from hot shift power take off (PTO). (Prefer NO drive shaft if	
U.	clearance allows)	
5.16.30	PTO: Hotshift PTO mounted to transmission	
5.16.31	Directional Valve:	
	System must be capable of operating plow and spreader at same time during snow	
a.	operation	
b.	Flow sharing	
	Spool valve with nominal flow ratings of 35- 45 gallons per minute (gpm)	
c. d.		
	With pressure to applied pressure drop not to exceed 275 psi at 45 gpm	
e. f.	All sections, pressure compensated	
	Electro-proportionally controlled Have flow control spools	
g.		
<u>h.</u>	The valve will have an adjustable main relief valve	
1.	All solenoids with manual overrides.	
j.	The directional valve configured as follows:	
	1. Auger - 2-way, single acting, 16 gpm	
	2. Spinner – 2-way single acting, 8 gpm	
	3. Bed Hoist – 3-way, double acting, 45 gpm power up/gravity down	
	4. Plow Lift – 3-way, single acting, 16 gpm power up/gravity down	
5 1 6 22	5. Plow angle – 4-way, double acting, 16 gpm power left/power right	
5.16.32	Hydraulic Reservoir:	
a.	The reservoir, a 30 gallon usable oil capacity	
b.	Reservoir of 10 gauge pickled steel construction and fully baffled	
с.	The exterior powder coated	
d.	The interior oil treated to prevent rust	
e.	A 2" suction port with suction strainer located on the frame side of the reservoir connecting	
	to a 2" full-flow ball valve.	
f.	The reservoir to be equipped with a magnetic drain plug	
g.	A sight level	
<u>h.</u>	Temperature gauge	
<u>i.</u>	A filler breather cap with metal strainer	
j.	An in-tank filter provided with 10-micron synthetic element	

k.	A combination oil level/temperature sender provided			
1.	A 25 psi pressure switch for the filter			
m.	The ground activated electric switches wired to indicator lights in the control panel. All			
	wiring to be weather protected			
5.16.33	Pressure Filter:			
a.	A 3,000 psi high-pressure hydraulic filter installed between the pump and the inlet of the			
	directional valve			
b.	The filter, a 10 micron synthetic element and a visual condition indicator			
с.	The filter assembly equipped with a 50 psi differential bypass and Society of Automotive			
	Engineers (SAE) 16 work ports			
d.	The filter needs to be located for easy access and maintenance of the filter element.			
e.	All filtration, U.S. manufactured.			
f.	All replacement elements for this system must be stocked by a local supplier.			
5.16.34	Hydraulic Quick Couplers for snow plow:			
a.	The hydraulic quick couplers for the reversing snowplow mounted to a cushion valve in an			
	ergonomic location on the plow hitch			
b.	The couplers, Parker/Pioneer 4000 series, ¹ / ₂ " couplers			
5.16.35	Hydraulic Quick Couplers for material spreader:			
a.	Quick couplers for the material spreader operation installed in the rear section of the lower			
	rub rail on the curbside of the dump body.			
b.	The connections laid out on 6" centers and consist of $\frac{1}{2}$ " pipe for the spinner, $\frac{3}{4}$ " pipe for			
	the conveyor supply, and $3/4$ " pipe for the common return			
с.	The pipe, schedule 80 and the lower rub rail reinforced with a ¹ / ₄ " plate			
d.	A ¹ / ₂ ", 4000 series Pioneer male coupler for the spinner pressure			
е.	A ³ / ₄ ", 5000 series Pioneer male coupler for the conveyor supply			
f.	A ³ / ₄ ", 6000 series Pioneer male for the common return			
g.	Dust caps installed on all the couplers.			
5.16.36	Hydraulic System Controls:			
a.	The controls for the central hydraulic system are of a modular design and consist of:			
	1. Material spreader control			
	2. Hoist			
	3. Plow control			
	4. A switch and indicator light package			
	5. The valve wiring harness			
	6. All hydraulic and auxiliary electrical controls are connected to an 80-amp butterfly type			
	manual re-set circuit breaker			
5.16.37	Spreader Control:			
a.	Certified Power electronic control for granular and pre wet material and liquid anti icing			
	tank shall operate current Sedgwick County owned equipment.			
b.	A display, capable of displaying two control channel application rates, ground speed,			
	spread width, and time/date simultaneously			
C.	Calibration of the spreader control that connects via a PS2 connection			
d.	d. The controller needs a R-232 port for connection to data retrieval/transmission devices,			
	and be specifically capable of interfacing with existing audio video link (AVL) or GPS			
	systems for data logging The operator access to calibrations may be limited by supervision			
e. f.				
	The system will operate in open or closed loop, and manual mode The cable ends with dust plugs installed			
g. h	The wiring is consistent in color code and orientation to receive material rate sensor			
<u>h.</u> i.	Include two keyboards for diagnostic and calibration of spreader control. If needed, deliver			
1.	to: Attention Rex Victory/Fleet Management, 1021 W. Stillwell St., Wichita, KS 67213			
i	The ground speed is to be enabled and calibrated when the truck(s) are delivered			
J. J.	The Stound Speed is to be endored and canorated when the truck(s) are derivered	1		

k.	The pre-wet on/off and low-pressure functions will terminate in a die-cast heavy-duty 4-	
	way electrical connector to fit county owned equipment.	
1.	The connector is located in the right rear corner post of the dump body, facing the front of	
	the truck	
m.	Exact location for sand spreader plug-in will be determined by Fleet Management	
n.	Components need to be moisture proof and require minimum maintenance	
0.	The winner bidder will provide operator training and assistance with calibration of the	
	systems at a location to be determined by the county.	
5.16.38	Hoist and Plow Control:	
a.	The electric controls for the hoist and plow are fully proportional	
b.	The hoist control with a center detent position to comply with OSHA standards and single	
	axis	
с.	The plow control will be dual axis with Power Float (to control weight of blade of surface)	
d.	Both controls are clearly labeled and mounted in a common enclosure	
e.	The wiring harness for all directional valve function will connect to a common valve drive	
	harness.	
f.	The NEMA 6P rated harness will have a connection block with LED's to indicate the	
	presence of voltage to the function. The valve drive harness, mounted inside the weather	
	resistant valve enclosure, and all functions clearly labeled.	
5.16.39	C. Switch and Indicator Panel – The switch panel will consist of 4-backlit circuit	
	breaker-type switches and four warning lights. The panel is configured but not limited to:	
a.	Single Pole Single Throw (SPST) rocker switch, 30 amps, for "Strobes". This switch is to	
	be battery hot at all times.	
b.	SPST rocker switch for "Air Tailgate". This and all other switches and warning lights are	
	to be switches powered through the ignition.	
с.	Double Pole, Double Throw (DPDT) rocker switch for "Tarp In" and "Tarp Out"	
d.	SPST rocker switch for pre wet system	
e.	Indicator light for "Oil Temp"	
f.	Indicator light for "Oil Level"	
g.	Indicator light for "Hydraulic Filter" in by-pass.	
5.16.40	Tow Package: Three of five units must be equipped with tractor package	
a.	3" Pintle hitch to be able to tow and operate county owned trailer (Trail King model	
	TK40RB) with air brakes	
b.	Pintle hitch to have air cushion to remove slack while towing.	

6. TIME IS OF THE ESSENCE

Time is of the essence for completion and delivery of vehicles in this contract. It is anticipated that delivery will be met in a timely fashion. Any delay in delivery described herein, shall result in the vendor being assessed liquidated damages. While the costs to the County in the event of a late delivery might not be easily and readily determinable, the liquidated damages are meant to include but not be limited to the County's increased maintenance costs for existing vehicles, necessary rental costs suffered by the County, lost employee productivity, and the County's inability to complete responsibilities, some of which are required by law and/or existing contracts.

Liquidated damages in the amount of two-hundred and fifty dollars (\$250.00) per vehicle per day shall be assessed for any late delivery. The County will deduct the total liquidated damages from the corresponding purchase order payment(s). At any point prior to the required delivery date, if the awarded vendor knows the vehicles will not be ready for delivery on the required delivery date, the vendor may contact the Sedgwick County Purchasing Department, which, based entirely upon its own discretion, may waive the liquidated damages for good cause shown. Any such request for a waiver shall be made by the vendor in writing and any such waiver by the Purchasing Department shall also be in writing.

County desires to have order delivered no later than October 15, 2015.

7. TENTATIVE TIMELINE

The following dates are provided for information purposes and are subject to change without notice. Contact Gunda Angelica at (316) 660-7262 to confirm any and all dates.

Distribution of Request for Bid to interested parties	March 18, 2015
Pre-bid meeting 11:00 a.m. CDT	March 25, 2015
Clarification, Information and Questions submitted in writing by 12:00 p.m. CDT	March 26, 2015
Addendum Issued	March 30, 2015
Sealed bids due before 1:45p.m. CDT	April 7, 2015
Evaluation Period	April 8-14, 2015
Board of Bids and Contracts Recommendation	April 16, 2015
Board of County Commission Award	April 22, 2015

8. QUESTIONS and CLARIFICATIONS

All requests for clarifications of the RFP process and document content should be directed to Gunda Angelica at <u>Gunda.Angelica@sedgwick.gov</u> and Penny Poland at <u>Penny.Poland@sedgwick.gov</u>. Questions must be submitted in writing by 12:00 p.m. CDT, March 26, 2015. Answers will be provided in written form as an addendum and will be posted on the County website at <u>www.sedgwickcounty.org/finance/purchasing.asp</u> by March 30, 2015. Vendors are responsible for checking the website and acknowledging any addenda in their response.

9. INDEMNIFICATION

To the fullest extent of the law, the provider, its subcontractor, agents, servants, officers or employees shall indemnify and hold harmless Sedgwick County, including, but not limited to, its elected and appointed officials, officers, employees and agents, from any and all claims brought by any person or entity whatsoever, arising from any act, error, or omission of the provider during the providers performance of the agreement or any other agreements of the provider entered into by reason thereof. The provider shall indemnify and defend Sedgwick County, including, but not limited to, its elected and appointed officials, officers, employees and agents, with respect to any claim arising, or alleged to have arisen from negligence, and/or willful, wanton or reckless acts or omissions of the provider, its subcontractor, agents, servants, officers, or employees and any and all losses or liabilities resulting from any such claims, including, but not limited to, damage awards, costs and reasonable attorney's fees. This indemnification shall not be affected by any other portions of the agreement relating to insurance requirements. The provider agrees that it will procure and keep in force at all times at its own expense insurance in accordance with these specifications.

10. TERMINATION

The County reserves the right to cancel the contract and discontinue services with a ninety (90) day written notice as a result of the failure of the contracted provider to provide acceptable services as delineated in the response to this document or if determined that services can be better provided by in-house or other sources. In the event of termination of this agreement as a result of a breach by contractor hereunder, the County will not be liable for any fees and may, at its sole option, award an agreement for the same services to another qualified firm with the best bid, or call for new bids and award an agreement for the same services to another qualified firm to provide services.

11. REQUEST FOR BID CONDITIONS

In submitting a response to this Request for Bid, vendors hereby understand the following:

- 1. Pricing offered in the bid document will be provided to other local governments and governments whom Sedgwick County regularly enters into cooperative agreements.
- 2. Sedgwick County reserves the right to reject any and/or all bids and responses to these and/or related documents, to accept any item(s) in the bids, to waive any irregularity in the bids, and further if determined to be non-responsive in any form, or if determined to be in the best interest of Sedgwick County.
- 3. Alternate bids (two or more bids submitted) will be considered for an award. Sedgwick County reserves the right to make the final determination of actual equivalency or suitability of such bids with respect to requirements outlined herein. The bids submitted, and any further information acquired through interviews, will become and is

to be considered a part of the final completed contract. If there is any variance or conflict, the bid specifications will control.

- 4. Bidders MUST return completed copies of the entire document to the Sedgwick County Purchasing Department, 525 North Main, 8th Floor, Suite 823, Wichita, KS 67203, on or before the date and time specified. Bids must be sealed in an envelope and marked with the firm name and address, bid number, bid opening date, and bid opening time. The time clock stamp, located in the Sedgwick County Purchasing Department will determine the time of receipt.
- 5. Bids submitted may not be withdrawn for a period of 60 days immediately following the opening of this Request for Bid. Prices MUST be free of federal, state, and local taxes unless otherwise imposed by a governmental body, and applicable to the material on the bid.
- 6. Sedgwick County interprets the term "Lowest Responsible and Best Bidder" as requiring Sedgwick County to: (a) choose between the kinds of materials, goods, wares, or services subject to the bid, and (b) determine which bid is most suitable for its intended use or purpose. Sedgwick County can consider, among other factors, such things as the availability of service(s), part(s) material(s) and/or supply(s), warranty, maintenance, freight costs, performance of product and labor cost of items upon which bids are received.
- 7. All requested information must be supplied. If bidders cannot respond to any part of this request, bidders should state the reason they cannot respond and note an exception. Bidders may provide supplemental information to assist Sedgwick County in analyzing its bid.
- 8. If the bidder refuses or fails to make deliveries of the materials within the times specified on the face of the Request for Bid or purchase order, Sedgwick County may, by written notice, terminate the contract or purchase order.
- 9. The bidder will certify and warrant that goods, personal property, chattels, and equipment sold and delivered are free and clear of any and all liens, or claims of liens, for materials or services arising under, and by virtue of the provisions of K.S.A. Sections 58-201, et seq., and any other lien, right, or claim of any nature or kind whatsoever.
- 10. The successful bidder will hold and save Sedgwick County, and its officers, agents, servants/employees harmless from liability of any patented, or unpatented invention, process, article, or appliance manufactured, or used in the performance of the contract, including its use by Sedgwick County. Vendors working on county property or on behalf of County will be required to carry minimum insurance listed in bid document.
- 11. All items furnished, if applicable, must be the best of their respective kinds, and will be free from defects in material and workmanship. Items will be subject to County inspection and approval at any time within 30 days after delivery. If a substitution is made, it will be the decision of a Sedgwick County representative to determine if it is of equal quality. Items furnished must be manufactured in compliance with all existing legal or governmental directives.
- 12. Unless specified otherwise, all items bid are to be as a minimum but not necessarily limited to: new, current model year, and untitled prior to shipping and/or installation.
- 13. Sedgwick County is desirous of allowing as many Kansas vendors as possible the opportunity to participate including minority men and women-owned businesses, and small businesses in the roles of providing goods and services to Sedgwick County. If your company does not fall into any of these categories, your efforts to contract with vendors who do fall into these categories are appreciated. Construction projects utilizing subcontractors requires a subcontracting worksheet. Contact purchasing department for details.
- 14. Contracts entered into on the basis of submitted bids are revocable if contrary to law.

- 15. County reserves the right to enter into agreements subject to the provisions of the Cash Basis Law (K.S.A. 10-1112 and 10-1113), the Budget Law (K.S.A. 79-2935). Agreements shall be construed and interpreted so as to ensure that the County shall at all times stay in conformity with such laws, and as a condition of agreements the County reserves the right to unilaterally sever, modify, or terminate agreements at any time if, in the opinion of its legal counsel, the Agreement may be deemed to violate the terms of such law.
- 16. The Bidder agrees to comply with K.S.A. 44-1030.
 - a. The contractor shall observe the provisions of the Kansas act against discrimination and shall not discriminate against any person in the performance of work under the present contract because of race, religion, color, sex, disability, national origin, or ancestry;
 - b. In all solicitations or advertisements for employees, the contractor shall include the phrase, "equal opportunity employer," or a similar phrase to be approved by the commission;
 - c. If the contractor fails to comply with the manner in which the contractor reports to the commission in accordance with the provisions of K.S.A. 44-1031 and amendments thereto, the contractor shall be deemed to have breached the present contract and it may be canceled, terminated or suspended, in whole or in part, by the contracting agency;
 - d. If the contractor is found guilty of a violation of the Kansas act against discrimination under a decision or order of the commission which has become final, the contractor shall be deemed to have breached the present contract and it may be canceled, terminated or suspended, in whole or in part, by the contracting agency; and
 - e. The contractor shall include the provisions of subsections (a) through (d) in every subcontract or purchase order so that such provisions will be binding upon such subcontractor or vendor.
- 17. All project participants, consultants, engineers, contractors and subcontractors, must comply with all applicable Federal, State and County laws pertaining to contracts entered into by governmental agencies. All participants must comply with the Americans with Disabilities Act (ADA), including the 2008 ADA Amendments Act, and 2010 ADA Standards for Accessible Design.
- 18. Contractors/subcontractors performing new construction, maintenance, alterations, or additions to Sedgwick County buildings or facilities must comply with building guidelines/codes, and the 2010 ADA Standards for Accessible Design. Any violation of the provisions of the ADA or 504, or specification deficiencies, should be reported to the county's ADA coordinator. Failure to notify the county's ADA coordinator for remedy may be considered a breach of contract and may be grounds for cancellation, termination for suspension, in whole or in any part of the contract. All construction plans will have the county's ADA coordinator approval prior to beginning any work.
- 19. Contractors/vendors providing services to the public on behalf of Sedgwick County will agree that all personnel in their employment that have direct contact with the public will attend ADA Awareness and Sensitivity training provided by Sedgwick County or the Independent Living Resource Center. Training should be coordinated through the county's ADA coordinator, (316) 660-7052 and evidence of training shall be provided to the county's ADA coordinator. Any violations of the provisions of ADA or section 504, will be deemed a breach of contract and be subject to termination of contract.
- 20. The successful bidder may have access to private or confidential data maintained by the County to the extent necessary to carry out its responsibilities of the contract. Contractor shall be responsible for compliance with the privacy provision of the Health Insurance Portability and Accountability Act (HIPAA) and shall comply with all other HIPAA provisions and regulations applicable. If the successful bidder is a business associate as that term is defined under HIPAA, the contract shall include the County's standard business associate addendum. A copy of that standard addendum is available on request.
- 21. The bidder responding to this bid solicitation proposes to furnish all materials, labor, supplies, equipment and incidentals necessary to provide the equipment/materials/services described herein in accordance with the Notification of Solicitation (if applicable), Request for Information (if applicable), Request for Bid, Addenda, Contract, Bonds, Insurance, Plans, Specifications, any Instructions, Mandatory Requirements and Conditions.

- 22. Unless specified elsewhere in the document, all prices quoted must be F.O.B. Destination, Freight Prepaid and Allowed, which will include all delivery, handling, and any other charges related to delivery including surcharges.
- 23. It will be understood that the bidder's sureties and insurers, as applicable, are subject to the approval of the County.
- 24. Prior to a vendor being awarded a contract, Domestic (Kansas) corporations shall 1) furnish evidence of good standing in the form of a Certificate signed by the Kansas Secretary of State. Foreign (non-Kansas) corporations shall furnish evidence of authority to transact business in Kansas, in the form of a Certificate signed by the Kansas Secretary of State; and 2) a copy of the Corporation Resolution evidencing the authority to sign the Contract Documents, executed by the Corporation's Secretary or Assistant Secretary.
- 25. Sedgwick County will not award to any vendor that is currently listed in the exclusion records of the SAM (System for Award Management) website maintained by the General Services Administration (GSA) or to any vendor presently debarred, suspended, proposed for debarment, or declared ineligible for the award of contracts by any Federal agency.
- 26. Upon award, the bidder agrees to execute and deliver to the County a contract in accordance with the contract documents (if applicable) within ten days of notice of the award to the bidder. The bidder agrees that the surety/deposit given concurrently herewith will become the property of the County in the event the bidder fails to execute and deliver such contract within the specified time. In the further event of such failure, the bidder will be liable for the County's actual damages that exceed the amount of the surety.
- 27. It will be understood that time is of the essence in the bidder's performance. The bidder agrees that the County's damages would be difficult or impossible to predict in the event of a default in the performance hereof; and it is therefore agreed that if the bidder defaults in the performance of the contract documents, the bidder will be liable for payment of the sums stipulated in the contract documents as liquidated damages, and not as a penalty.
- 28. The bidder hereby certifies that he or she has carefully examined all of the documents for the project, has carefully and thoroughly reviewed this Request for Bid, has inspected the location of the project (if applicable), and understands the nature and scope of the work to be done; and that this bid is based upon the terms, specifications, requirements, and conditions of the Request for Bid documents. The bidder further agrees that the performance time specified is a reasonable time, having carefully considered the nature and scope of the project as aforesaid.
- 29. It will be understood that any bid and any and/or all referencing information submitted in response to this Request for Bid will become the property of Sedgwick County, and will not be returned. As a governmental entity, Sedgwick County is subject to making records available for disclosure after Board of County Commission approval of the recommendation.
- 30. Sedgwick County will not be responsible for any expenses incurred by any vendor in the development of a response to this Request for Bid including any onsite (or otherwise) interviews and/or presentations, and/or supplemental information provided, submitted, or given to Sedgwick County and/or its representatives. Further, Sedgwick County will reserve the right to cancel the work described herein prior to issuance and acceptance of any contractual agreement/purchase order by the recommended vendor even if the Board of County Commissioners has formally accepted a recommendation.
- 31. By submission of a response, the bidder agrees that at the time of submittal, he or she: (1) has no interest (including financial benefit, commission, finder's fee, or any other remuneration) and will not acquire any interest, either direct or indirect, that would conflict in any manner or degree with the performance of bidder's services, or (2) benefit from an award resulting in a "Conflict of Interest". A "Conflict of Interest" will include holding or retaining membership, or employment, on a board, elected office, department, division or bureau, or committee sanctioned by and/or governed by the Sedgwick County Board of County Commissioners. Bidders

will identify any interests, and the individuals involved, on separate paper with the response and will understand that the County, at the discretion of the Purchasing Director in consultation with the County Counselor, may reject their bid/quotation. The bidder certifies that this bid is submitted without collusion, fraud or misrepresentation as to other bidders, so that all bids for the project will result from free, open and competitive bidding among all vendors.

- 32. Sedgwick County will issue a purchase order/contract for the acquisition of products/services specified as a result of an award made in reference to this document. Contract documents will be subject to any regulations governed by the laws of the State of Kansas and any local resolutions specifically applicable to the purchase.
- 33. Any dispute arising out of the contract documents or their interpretation will be litigated only within the courts of the State of Kansas. No prepayment of any kind will be made prior to shipment. Payment will be made upon verification of delivery, compliance with specifications, assurance that the product/service performs as specified and warranted, and receipt of correct invoicing.
- 34. Sedgwick County will accept responses transmitted via a facsimile unless stated to the contrary within this document. Bids must be received prior to the time and dates listed to be considered responsive. Sedgwick County will not accept late responses and will return them to the sender. Further, Sedgwick County will NOT: (1) guarantee security of the document received; (2) be held responsible for Bids which are NOT legible (and may choose to reject such responses); and, (3) guarantee that the receiving facsimile machine will accept transmission or that phone lines are functioning and available for transmission. Submitting a bid response via facsimile does NOT relieve the bidder of: (1) responsibilities stated in the document (such as attendance at a mandatory pre-bid conference); (2) providing non-paper informational items which must be returned with the response (diskettes, large drawings, photographs, models, etc.); and, (3) providing original copies of bid sureties (bonds, certificates of insurance, etc.).

12. GENERAL CONTRACT PROVISIONS

The following appendix is language the County requires for all contracts that are entered in to (if duplication exist, previous sections prevail). <u>http://www.sedgwickcounty.org/purchasing/pdf_files/General_Contract_Provisions.pdf</u>.

13. PAYMENT AND INVOICE PROVISIONS

Payment for all specified products/services to the successful vendor will be made following:

- Satisfactory delivery of all products and/or services described within these specifications
- Receipt of invoice. Invoices with Purchase Order number and delivery location shall be submitted to <u>AP_invoices@Sedgwick.gov</u> or mailed to 525 N. Main St., Suite 823, Wichita, KS, 67203. Detailed provisions can be found at: <u>http://www.sedgwickcounty.org/purchasing/payment_and_invoice_provisions.pdf</u>

14. BID CONTENT

The bid response should be organized in the following format and information sequence:

- 1. State full name and address of your organization and provide a brief description of your firm, including qualifications, experience, quality control, and the demonstration of your ability to deliver a quality product.
- 2. Provide a list of four (4) past or current client references; include organization, address, date of services, scope of services/product, contact person, telephone number, and an email address.
- 3. Clearly address in sequential order each of the minimum qualifications listed in Section 3.
- 4. Clearly address in sequential order each of the minimum requirements/specifications listed in Section 5. *Proposers must clearly delineate and describe in detail any exceptions to the requirements and specifications.*
- 5. Provide copy of Insurance.
- 6. Provide complete warranty information.
- 7. Prior to a vendor being awarded a contract, Domestic (Kansas) corporations shall 1) furnish evidence of good standing in the form of a Certificate signed by the Kansas Secretary of State. Foreign (non-Kansas) corporations shall furnish evidence of authority to transact business in Kansas, in the form of a Certificate signed by the Kansas Secretary of State; and 2) a copy of the Corporation Resolution evidencing the authority to sign the Contract Documents, executed by the Corporation's Secretary or Assistant Secretary
- 8. Sign and return the completed Bid Response Form that is provided on page 15.

BID RESPONSE FORM #15-0032 FIVE (5) TANDEM AXLE DUMP TRUCKS

The undersigned, on behalf of the Proposer, certifies that: (1) this offer is made without previous understanding, agreement or connection with any person, firm, or corporation submitting a bid on the same project; (2) is in all respects fair and without collusion or fraud; (3) the person whose signature appears below is legally empowered to bind the firm in whose name the bid is entered; (4) they have read the complete Request for Bid and understands all provisions; (5) if accepted by the County, this bid is guaranteed as written and amended and will be implemented as stated; and (6) mistakes in writing of the submitted bid will be their responsibility.

NAME			
DBA/SAME			
CONTACT			
ADDRESS			
PHONE	FAX	He	OURS
TAX PAYER I.D. NUMBER		STATE INCC	RPORATED
COMPANY WEBSITE ADDRESS		E-MAIL	
NUMBER OF LOCATIONS	NUMBER OF	F PERSONS EMPLO	YED
TYPE OF ORGANIZATION: Public Co	prporation Pri	vate Corporation	Sole Proprietorship
PartnershipSmall Business	Manufacturer	Distributor	_Retail Dealer
General Nature of Business	_ FEIN/SS #	W-9 include	ed
Not a Minority Owned Business	Minority Owned Bu	usiness: Certific	ation#
African AmericanAsianHispanio	c Native America	an Other Wo	oman Owned Business

ACKNOWLEDGE RECEIPT OF ADDENDA: All addendum(s) are posted to our RFQ/RFP web page and it is the vendor's responsibility to check and confirm all addendum(s) related to this document by going to www.sedgwickcounty.org/finance/purchasing.asp.

NO.____, DATED _____; NO.____, DATED _____; NO.____, DATED _____;

Qty.	Description	Unit Price	Extended Price
2 ea.	Tandem Axle Dump Truck	\$	\$
3 ea.	Tandem Axle Dump Truck with tow package (Specification # 5.16.40)	\$	\$
Make/M	lodel		
1 ea.	Operator manuals for truck and for all equipment mounted on vehicle	\$	\$
1 ea.	Part manuals for truck and for all equipment mounted on vehicle.	\$	\$
1 ea.	Repair and maintenance manual, including wire schematics.	\$	\$
		Grand Total	\$
Deliver	y Date:		